

HSAJET® TIPC15 Premium

TOUCH PRINT CONTROLLER FOR HP INKJET

Windows driven controller with
database connectivity
for fully variable imprints

HSAJET® Premium Touch Printer Controller utilizes HP Thermal InkJet 2.5 technology

The Premium TIPC15 is the most compact stand alone touch controller available in the market that enables a print height of up to 100 mm (4").

The controller builds on the PCI express based HSAJET® CB6e controller board.

Industrial casing

The black anodised aluminium frame and steel case provide extra protection for harsh industrial environments.

HSAJET® software

The TIPC15 is delivered with Windows operating system and InkDraw 3 printing software.

InkDraw is our software specially designed for coding/ marking and commercial printing applications.

All HSAJET® software solutions provide the features needed for their respective markets, as well as an easy to use, intuitive user interface.

Advanced software features

Stitching accuracy down to pixel level means printable objects can be located anywhere on the canvas without limitation.

All TIPC15 software packages offer a flexible ink saving feature providing up to a 75% ink saving in addition to fully variable resolution.

Remote control

The comprehensive communication protocol allows you to control the unit remotely. Remote management is done through ethernet or serial connection.



Premium series

In addition to the TIPC15 Premium controller, we offer the Premium MiniTouch with a print height of 2" or the individually configured PC-controllers built on the CB6e controller board offering a print height of up to 8".

Premium printhead

The centrepiece innovation of the Premium series is the hard anodised aluminium Premium printhead.

The CrN treated aluminium footplate of the printhead has a wear resistant surface with high conductivity and low friction. Ink cartridges are easy to replace and are held in the correct position without the use of a latch.

Print at breakthrough speeds of up to 300 m/min in 300 x 150 dpi

- GRAPHICS
- COUNTERS
- SHIFT CODES
- VARIABLE TEXT
- FIXED TEXT
- 1D & 2D CODES*
- DATE & TIME (REAL-TIME & ADJUSTED)
- WINDOWS FONTS

* For information on specific barcodes please go to www.hsasystems.com

Technical Details TIPC15-HP PREMIUM

HSAJET TIPC15 PREMIUM TOUCH PRINT CONTROLLER

Technology

HP TIJ 2.5

Print height

With crypto key up to 4" (101.6 mm)

Printheads

HSAJET® Premium printheads (see flyer)
Connect 2 printheads directly to the controller or use distributor box for connection of up to 8 single 1-pen printheads.

Print distance

0.5-5.0 mm depending on ink and speed, typically 0.5-2.0 mm (nozzle to print surface)

Voltage

100-240 VAC

Print buffer

64 MB

Screen

15" colour touch screen

Design software

InkDraw 3 incl. PDF

Optional:

Mail Tool incl. event/stacker,
Integration Tool, Event/4xStacker
(See InkDraw flyer)

Software menu language

English (multiple languages)

Print functions, e.g.

Database printing (XLSX, CSV, TXT, PDF)

User prompt

User defined print log

Error log

Print options

Variable DPI

Left/Right, Upside-down

Other side, Bidirectional

Inverted

Layout options

Object rotation in 90 deg intervals

Link field content

Works with mm/inch/point/pixel

Unlimited number of objects

Remote controlling via protocol, e.g.

Start/stop print job

Change field content per print

Change print preferences/parameters

Interface

RS232 (serial)

Ethernet (LAN) 100 Mbit (Standard)

USB 2.0

Control connection (SUB D15)

Encoder Input 3-33V (SUB D9)

In-/output 3-33 V (SUB D9)

Printhead connections (2x RJ45)

Complies with

CE directives

Housing

Black anodised aluminium frame

Stainless steel housing

Weight

8.1 kg / 17.8 lbs

Accessories

- Premium printheads (see other flyer)
- Distributor box
- Interface Box w/LED control signal f/CB6e
- USB Key / Stylus pen (included)
- Sensor and encoder
- Bridges and brackets
- Mountings (Inocon 53 mm)
- Adaptorplate for Inocon FLV-25/ FLV-40/ FLS30-S1 (included)


Vertical resolution (DPI)	Horizontal resolution 75-2400 DPI (variable)* speed examples (m/min)			
	75 DPI	300 DPI	600 DPI	2400 DPI
600 DPI	304	76	38	10
300 DPI high speed	608	152	76	19
300 DPI (row A)	304	76	38	10
300 DPI (row B)	304	76	38	10

*) Dependent on controller and software

TIPC15 Premium	PC configuration
Hard disk	256 GB SSD
RAM	8 GB
Processor	Intel I3-8100 3,6 GHz Quad Core
Printing Software	InkDraw 3 incl. PDF
Operating System	WIN10 64bit
TIPC15 Premium	Dimensions
Length	384 mm / 15.1"
Width	106 mm / 4.2"
Height	294 mm / 11.6"



Distributor box



CHECK OUR WEBSITE FOR THE LATEST VERSION OF THIS DATASHEET

DISTRIBUTOR:



HSA Systems (head offices)
DENMARK +45 6610 3401

HSA Systems (subsidiary offices)

FRANCE +33 1 4815 5050 | GERMANY +49 4331 203 9755

www.hsasystems.com | mail@hsasystems.com